



7313 Varna Avenue, North Hollywood, CA 91605
 Toll free: (800) 341-3165 Phone: (818) 503-0596
 Fax: (818) 503-0599 E-MAIL: info@skdrapes.com

www.sktheatricaldraperies.com

CURTAIN MACHINE SELECTOR GUIDE



Proud distributors of Automatic Devices products

CURTAIN MACHINE SELECTOR GUIDE									
Machine Type	Trademark or Name	Model No.	Control Circuit	Motor HP	Low Voltage Available	Max. No. Remote Switches	Max. One Way Cable Travel (ft) (A)	Listing	Page No.
DRAW	Autodrape	934	Versatile	1/4	Standard	Unl.	45	ETL	91
	Autodrape	1454	Versatile	1/3	Standard	Unl.	45	ETL	91
	Silver Service	2904	Versatile	1/2	Standard	Unl.	45	ETL	91
	Silver Service	2904-TV	Variable	1/2	Standard	Unl.	45		92
	Hercules	6504	Versatile	3/4	Standard	Unl.	45	ETL	91
	Hercules	6504-TV	Variable	3/4	Standard	Unl.	45		92
	Silver Service	2905	Versatile	1/2	Standard	Unl.	90	ETL	93
	Silver Service	2905-TV	Variable	1/2	Standard	Unl.	90		94
	Hercules	6505	Versatile	3/4	Standard	Unl.	90	ETL	93
	Hercules	6505-TV	Variable	3/4	Standard	Unl.	90		94
	Hercules	7005	Versatile	1	Standard	Unl.	90	ETL	93
	Hercules	7005-TV	Variable	1	Standard	Unl.	90		94
	Silver Service	2928, 2914, 2917, 2950, 2960, 2961, 2962, 2963	Versatile	1/2	Standard	Unl.	Unl.	ETL	89
	Silver Service		Versatile	1/2	Standard	Unl.	Unl.	ETL	90
LIFT	Autodrape	936	Intermediate	1/4	(C)	1	48	ETL	95
	Autodrape	1456	Intermediate	1/3	(C)	1	48	ETL	95
	Silver Service	2906	Intermediate	1/2	(C)	1	48	ETL	95
	Hercules	6506	Intermediate	3/4	(C)	1	48	ETL	95
	Autodrape	963	Intermediate	1/4	(C)	1	24	ETL	96
	Silver Service	2907	Versatile	1/2	Standard	Unl.	70	ETL	97
	Silver Service	2907-TV	Variable	1/2	Standard	Unl.	70		98
	Hercules	6507-TV	Variable	3/4	Standard	Unl.	70		98
	Hercules	7007	Versatile	1	Standard	Unl.	70	ETL	97
	Hercules	7007-TV	Variable	1	Standard	Unl.	70		98
	Hercules	8007	Versatile	1-1/2	Standard	Unl.	70	ETL	97
	Hercules	9007	Versatile	2	Standard	Unl.	70	ETL	97
	Hercules	9007-TV	Variable	2	Standard	Unl.	70		98
	Hercules	9507-TV	Variable	5	Standard	Unl.	55	ETL	99
GYM DIVIDER	Autodrape	933	Intermediate	1/4	(C)	1	54	ETL	100
	Autodrape	1453	Intermediate	1/3	(C)	1	54	ETL	100
	Silver Service	2903	Intermediate	1/2	(C)	1	54	ETL	100
	Hercules	6503	Intermediate	3/4	(C)	1	54	ETL	100
	Autodrape	1452	Intermediate	1/3	(C)	1	36	ETL	101
	Silver Service	2902	Intermediate	1/2	(C)	1	36	ETL	101
	Hercules	6502	Intermediate	3/4	(C)	1	36	ETL	101
SIDE MASKING	Autodrape	940	Versatile	1/4	Yes	Unl.	18	UL/ETL	102
	Autodrape	1460M	Versatile	1/3	Yes	Unl.	18	UL/ETL	102
	Silver Service	2910	Versatile	1/2	Yes	Unl.	18	UL/ETL	102
	Autodrape	936SFR	Versatile	1/4	Yes	1	24	UL/ETL	103
	Autodrape	963S	Versatile	1/4	Yes	1	48	UL/ETL	103
	Tom Thumb	873	Intermediate	1/30	No	1	18	ETL	105
	Tom Thumb	873-MCS	Versatile	1/30	Std.	Unl.	18	UL/ETL	105
	Tom Thumb	1003	Intermediate	1/8	No	1	18	UL	105
	Tom Thumb	1003-MCS	Versatile	1/8	Std.	Unl.	18	UL/ETL	105
DRAPERY	Tom Thumb	579	Variable	24W	Standard	Unl.	30	UL	104
	Tom Thumb	872	Intermediate	1/30	No	1	30	ETL	106
	Tom Thumb	872-MCS	Versatile	1/30	Standard	Unl.	30	UL/ETL	106
	Tom Thumb	1002	Intermediate	1/8	No	1	30	ETL	107
	Tom Thumb	1002-MCS	Versatile	1/8	Standard	Unl.	30	UL/ETL	107
	Tom Thumb	1002-VED	Versatile	1/8	Standard	Unl.	17	UL/ETL	108
	Tom Thumb	1002-VEA	Versatile	1/8	Standard	Unl.	30	UL/ETL	108

(A) Based on diameter of drive and size cable normally supplied with machine (see appropriate catalog page). Additional cable travel is obtainable by increasing size of drive and/or gear. To determine maximum track length useable with particular machine, cable travel is doubled (e.g. 36' cable travel indicates 72' curtain separation or 72' track in 2-36' sections, but figure does not include stacking space). (B) Based on loft block diameter of 6" minimum and over. (C) Low voltage available only if magnetic control system is supplied, at additional cost. (D) Discuss application with factory. * Variable Speed. Vertical lift machines are not to be used for the lifting, supporting, or transporting of people, or over areas where people are present unless suitable safety devices are installed.

NOTE: Special machines can be designed to job specification upon request. Also, most of our machines can be mounted upside down if necessary. However, we should be so advised when order is placed with us.